

VOLKSWAGEN TRANSPORTER

NEW DEVON AEROSPACE ROOF

INSTRUCTIONS FOR USE

The principal function of this roof is to provide comfortable sleeping accommodation for two people, either adults in a double bed or small children in two separate single beds.

When open the roof takes up a position with an incline downwards front to back.

While operating the roof, it is advisable to open the roof vent and windows or sliding door to allow expansion or compression of air within the vehicle.

Elevating the Roof

1. Disengage the two internal locking catches. Push thumb button upward and pull the bottom of catch towards you. With the two halves of the catch separated fold the top part up against the roof.

2. Stand facing forward. Place one hand on each side of the roof as far forward as bed cushion permits and push up evenly.

The gas struts on exterior will assist lift until forward end of roof is fully up.

3. A light push to the roof, centrally and rearward, will now fully open the roof. No further action is required.

Closing the Roof

1. Stand centrally, rearward facing. Pull the two straps evenly down and towards you until rear of roof is down.

2. Release either of the two straps and with free hand, hold pull down handle at rear of roof vent. Release 2nd strap. Turn to forward facing and get two handed grip on handle, hands apart.

3. Pull down evenly and slowly. The roof will lower gently until front is about one foot from closed. Pull the flexible material sides in over the front bed boards.

4. Using the roof handle, pull roof down and towards you sharply.
5. Engage the two locking catches. No further action is required.

APRIL 1984

DEVON CONVERSIONS LTD.
Vulcan Works
Water Lane
Exeter
Devon, EX2 8BY